

EYONGPV LIMITED

Add:Huidebao Industrial park, Guanguang RD, Guangming Develop Area, Shenzhen,China

Tel.:+86-755-29420722; Fax.: 86-755-29420733

sales@eyongpv.com ; http://www.eyongpv.com



400W Foldable solar charger

High efficiency SunPower 400W ,fabric folding solar panel

We can do different plug according to customer requested

Light weight, portable to take out.

Model No : EYB400-18SP

Product specification		Product photo
Bag material	600D	
Bag color	Camouflage color or OEM color	
Open size	2220*1080mm	
Folding size	545*545mm	
Folding thickness	35mm	
Folding types	2*4	
Net weight	8.1 KG	
Solar panel		
Solar Cell	Sunpower	
Efficiency rate	22.6%	
Each Solar panel size	526*534*3mm	
Total solar panel qty	8 PCS	
Maximum power(Pm)	400W	
Power Tolerance	-5%	
Voltage at max power(Vmp)	18V	
Current at max power(Imp)	22.22A	
Open circuit voltage(Voc)	22V	
Short circuit current(Isc)	24A	
Operating Temperature	- 40℃ — +85℃	
Maximum System Voltage	1000V	
Maximum Series Fuse Rating	25A	
Certifications	CE、 FCC、 ROHS	
Standard Test Condion	Irrandiance 1000W/m ² Module temperature 25℃,AM=1.5	
Power is not less than 90% in 10 years and 80% in 25 years		
Temperature Characteristics		
Noct :46℃ ± 2℃		
Temperature Coefficient of Power (P): -0.38%/K		
Temperature Coefficient of Voltage (Voc): -132.5 mV/K		
Temperature Coefficient of Current (Isc): (-1.8mV /°C)		