## **EYONGPV LIMITED**

Add:Huidebao Industrial park, Guanguang RD, Guangming Develop Area, Shenzhen, China

Tel.:+86-755-29420722; Fax.: 86-755-29420733

sales@eyongpv.com; http://www.eyongpv.com

## 500W Foldable solar charger

High efficiency SunPower 500W ,fabric folding solar panel

We can do different plug according to customer requested

Light weight, portable to take out.

Model No : EYB500-36SP

Product specification

1 Todact Specification	
Bag material	600D
Bag color	Camouflage color or OEM color
Open size	2840*1100mm
Folding size	560*560mm
Foldinjg thickness	70mm
Folding types	2*5
Net weight	12.25 KG
Solar panel	
Solar Cell	Sunpower
Efficiency rate	22.6%
Each Solar panel size	526*534*3mm
Total solar panel qty	10 PCS
Maximum power(Pm)	500W
Power Tolerance	-5%
Voltage at max power(Vmp)	36V
Current at max power(Imp)	13.89A
Open circuit voltage(Voc)	43.2V
Short circuit current(lsc)	15.1A
Operating Temperature	- 40℃ —+85℃
Maximum System Voltage	1000V
Maximum Series Fuse Rating	15A
Certifications	CE、FCC、ROHS
Standard Test Condtion	Irrandiance 1000W/m² Module temperature 25℃,AM=1.5

Power is not less than 90% in 10 years and 80% in 25 years

## **Temperature Characteristics**

Noct :46℃ ± 2℃

Temperature Coefficient of Power (P): -0.38%/K

Temperature Coefficient of Voltage ( Voc ): -132.5 mV/K

Temperature Coefficient of Current ( lsc ): (-1.8mV /°C)

## Product photo





