

# EYONGPV LIMITED

Add:Huidebao Industrial park, Guanguang RD, Guangming Develop Area, Shenzhen,China

Tel.:+86-755-29420722; Fax.: 86-755-29420733

sales@eyongpv.com ; http://www.eyongpv.com

## 150W Foldable solar charger

High efficiency SunPower 150W ,fabric folding solar panel

We can do different plug according to customer requested

Light weight, portable to take out.

Model No : EYB150-18SP

### Product specification

Bag material	600D
Bag color	Camouflage color or OEM color
Open size	1740*540mm
Folding size	290*540mm
Thickness	30mm
Folding types	1*5
Net weight	3.74 KGS

### Solar panel

Solar Cell	Sunpower
Efficiency rate	22.6%
Each Solar panel size	400*410*3mm
Total solar panel qty	6 PCS
Maximum power(Pm)	150W
Power Tolerance	-5%
Voltage at max power(Vmp)	18V
Current at max power(Imp)	8.33A
Open circuit voltage(Voc)	22V
Short circuit current(Isc)	9.15A
Operating Temperature	- 20°C — +60°C
Maximum System Voltage	1000V
Maximum Series Fuse Rating	12A
Certifications	CE、FCC、ROHS
Standard Test Condion	Irrandiance 1000W/m <sup>2</sup> , Module temperature 25°C,AM=1.5

Power is not less than 90% in 10 years and 80% in 25 years

### Temperature Characteristics

Noct :46°C ± 2°C	
Temperature Coefficient of Power (P):	-0.38%/K
Temperature Coefficient of Voltage ( Voc ):	-132.5 mV/K
Temperature Coefficient of Current ( Isc ):	(-1.8mV /°C)

### Product photo

